


InterLocked Flexible Metal Liquid Tight Conduit (YF-806)

InterLocked Liquid Tight Metal Conduit
Most suitable for frequent bending and movements.

With increased IP protection when used with Delikon Liquid Tight fittings.



Heavy Duty PVC Coating is sucked into the metal corrugation during the extrusion process, thus preventing the PVC cover from slipping off the metal surface or wrinkling even bent repeatedly.

Liquid Tight Conduit

InterLocked Steel Strip

Interlocked Construction prevents unraveling under frequent bending & movements.

Type	Trade Size	I.D. (mm)		O.D. (mm)		Min. Bending Radius (mm)	Meters/Coil
		MIN.	MAX.	MIN.	MAX.		
YF-80602	1/4"	6.2	6.7	11.4	11.9	50	100
YF-80603	3/8"	12.5	13.0	17.8	18.3	60	50
YF-80604	1/2"	16.1	16.6	21.3	21.8	80	50
YF-80606	3/4"	20.7	21.3	25.9	26.4	100	30
YF-80610	1"	26.3	26.8	33.3	33.8	150	30
YF-80612	1-1/4"	35.0	35.5	42.6	43.1	180	20
YF-80614	1-1/2"	40.0	40.5	47.6	48.0	220	20
YF-80620	2"	51.0	51.5	60.3	60.8	250	15
YF-80624	2-1/2"	63.0	63.7	72.2	73.0	300	10
YF-80630	3"	78.0	78.8	88.2	89.0	450	10
YF-80640	4"	101.8	102.8	113.2	114.0	600	5
YF-80650	5"	126.0	128.0	133.0	135.0	750	5
YF-80660	6"	149.0	151.0	156.0	158.0	900	5

Interlocking flexible liquid tight conduit is made from a helical ribbon of zinc coated strip, and externally coated in smooth and durable PVC. Resistant to most types of oils and greases, interlocked liquid tight conduit provides good flexibility and excellent mechanical resistance when subjected to traction stresses. Most suitable for industry machineries cables protection.