

**G, Metric, NPT, PG Thread Liquid Tight Nylon Connector, Polyamide Fittings (YNB)**

Material: **Polyamide** (PA, nylon)

Delikon Liquid Tight Nylon Connector is lightweight and resistant to corrosion, abrasion, chemicals, and high voltages, making it ideal for use with liquid tight flexible metal conduit LFMC, liquid tight flexible non metallic conduit LFNC, coated flexible metal conduit, and corrugated flexible Polyamide conduit. Delikon Liquid Tight Nylon Connector is available with G, Metric, NPT, and PG Thread, and is available from 1/4" to 4"



Model No.	Trade Size		Model No.	Trade Size
<b>YNB-02B</b>	1/4"		<b>YNB-14B</b>	1-1/2"
<b>YNB-03B</b>	3/8"		<b>YNB-20B</b>	2"
<b>YNB-04B</b>	1/2"		<b>YNB-24B</b>	2-1/2"
<b>YNB-06B</b>	3/4"		<b>YNB-30B</b>	3"
<b>YNB-10B</b>	1"		<b>YNB-40B</b>	4"
<b>YNB-12B</b>	1-1/4"			
G, Metric, NPT, and PG Male or Female Thread				

Delikon Liquid Tight Nylon Connector offers superior wear resistance, impressive mechanical strength and durability, while its lightweight makes it ideal for Transportation Industry Wire Harness. In marine applications, where constant exposure to saltwater accelerates metal corrosion, Delikon Liquid Tight Nylon Connector provides **long-lasting performance** without degrading. Similarly, in industrial machinery, Delikon Liquid Tight Nylon Connector excels in environments exposed to moisture, chemicals, and extreme conditions, ensuring durability and reducing maintenance costs.